



Product Data

Model	Bicycles	Width	Depth	Height
SD03	3	48 in	54 in	36 in
SD04	4	62.5 in	54 in	36 in
SD05	5	77 in	54 in	36 in
SD06	6	91.5 in	54 in	36 in
SD07	7	106 in	54 in	36 in
SD08	8	120.5 in	54 in	36 in



SD05-LL-G shown

Locking Options, per bike position [* = recommended]

- LL Locking Loop* Fixed loop for locking rear wheel
- LA Locking Arm Hinged loop for locking rear triangle
- NL None No locking provisions

Finish Options [* = recommended]

- G Galvanized * Hot dipped
- P Powder Coated Color frames, galvanized bike trays

Mounting Options

Optional, order four fasteners [(2) 1/2" x 4-1/2" and (2) 1/2" x 5-1/2"] per rack only if racks are to be mounted to concrete

- ZBOLT-SD Concrete Zinc Wedge Anchor fastener
- SSBOLT-SD Concrete Stainless Steel Wedge Anchor fastener

Construction

- Frames and crossbars .120 carbon steel tubing (1" x 1", 1" x 2", 2"x 2")
- Rear tray supports 1"x1"x1/8" angle iron
- Crossbar tabs 1/4" steel
- Minor pieces 1" x 2" x .120" wall steel
- Bicycle trays .120" mild steel sheet
- Welding MIG
- Mounting holes 11/16", one per corner (4 total)

Assembly (racks are shipped knocked down)

- Time 15-25 minutes /rack
- Tools Cordless driver recommended.
3/4" socket and open-end wrenches.
Philips-head screwdriver or driver bit.